



TECHNISCHES DATENBLATT					Ausgabe	
<i>TECHNICAL DATA SHEET</i>					<i>Edition</i>	
					Jan. 10	
		0799 - CPD GTX-W				
Produktname <i>Product trade name</i>	03/GEG	Bitutex® - Stargrid™				
Produkt-Ident <i>Product-ID-No.</i>		100 / 100 - 30				
Textiltyp <i>Textile type</i>	Polymer	MD Glass	E-Glass			
Ausrüstung <i>Coating type</i>		bituminös <i>bituminous</i>				
Farbe <i>Colour</i>		schwarz <i>black</i>				
Schmelzpunkt <i>Melting point</i>	C°	Glas Glass	850-900			
Maschenfüllung <i>Mesh filling</i>	g/m²	Glas 40	Glaslunte			
Gitteröffnung <i>Aperture size</i>	mm	Glas 40	<i>Glass texture</i>			
Höchstzugkraft <i>Tensile strength at max load</i>	kN/m	MD 30	(± 3)			
Dehnung <i>Elongation</i>	%	CMD 30	(± 3)			
Übliche Bezugskraft <i>Usual force at strain</i>	kN/m	MD 110	(- 10)		DIN EN ISO 10319	
Flächengewicht <i>Mass per unit area</i>	g/m²	CMD 110	(- 10)		DIN EN ISO 10319	
Rollenmasse <i>Roll dimensions</i>	±10%	@	2%	3%	5%	10%
Vorgesehene Funktion <i>Intended use</i>	R	MD 88	107	n	n	
		CMD 78	103	n	n	
			500	(± 40)		DIN EN ISO 9864
		Breite <i>width</i>	Länge <i>length</i>	Gewicht <i>weight</i>		
		2,20 m	100 m	115 kg		
		Bewehrung von Erdbauwerken				
		<i>Soil reinforcement</i>				

Standard tolerances and technical developing change reserved
 The latest version of all Technical Data Sheets is available at www.synteen.de.