



TECHNISCHES DATENBLATT		Ausgabe	
<i>TECHNICAL DATA SHEET</i>		<i>Edition</i>	
		<i>Jan. 10</i>	
		0799 - CPD GGR	
Produktname <i>Product trade name</i>		Sympaforce®	
Produkt-Ident <i>Product-ID-No.</i>		80 / 30 - 20 N	
Textiltyp <i>Textile type</i>		GELN08030	Farbcode: pink + blau <i>colour code: pink + blue</i>
Ausrüstung <i>Coating type</i>	Polymer	MD PET	Polyester high tenacity
Farbe <i>Colour</i>		CMD PET	Polyester high tenacity
Schmelzpunkt <i>Melting point</i>		PVC <i>PVC</i>	
Vliesstoff <i>Non-Woven</i>	C	schwarz <i>black</i>	
Gitteröffnung <i>Aperture size</i>		PET 250-260	
Höchstzugkraft <i>Tensile strength at max load</i>	g/m ²	kein <i>none</i>	
Dehnung <i>Elongation</i>		MD 20 (± 3,0)	CMD 20 (± 3,0)
Übliche Bezugskraft <i>Usual force at strain</i>	mm	MD 88 (- 8,0)	DIN EN ISO 10319
Flächengewicht <i>Mass per unit area</i>		CMD 37 (- 7,0)	
Rollenmasse <i>Roll dimensions</i>	kN/m	MD 11 (± 3,0)	DIN EN ISO 10319
Vorgesehene Funktion <i>Intended use</i>		CMD 12 (± 3,0)	
	%	@ 2% 3% 5% 10%	
		MD 16 19 25 57	
	kN/m	CMD 6 7 9 20	
		400 (± 32)	DIN EN ISO 9864
	g/m ²	Breite <i>width</i>	Länge <i>length</i>
		5,00 m	100 m
	±10%		220 kg
		R	Bewehrung von Erdbauwerken <i>Soil reinforcement</i> 

Standard tolerances and technical developing change reserved
 The latest version of all Technical Data Sheets is available at www.synteen.de.